



**Product** Shishu Stitch **Color** 106646 Limestone **Collection** Embodied Beauty **Backing** CQuest™BioX

[-CO2]

**Installation Method**



Herringbone Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

Product Specifications		
Product Number	137480AK0Q	
Product Construction	Tufted Textured Loop	
Yarn System	Post-Consumer Content Nylon	
Yarn Manufacturer	Universal	
Dye Method	100% Solution Dyed	
Soil/Stain Protection	Protekt <sup>2</sup> ®	
Preservative Protection	No Added Preservatives	
	Imperial	Metric
Tufted Yarn Weight	12 oz/yd <sup>2</sup>	407 g/m <sup>2</sup>
Machine Gauge	1/12 in	47.2 ends/10cm
Pile Height	0.13 in	3.3 mm
Pile Thickness	0.065 in	1.7 mm
Stitches	17.5 /in	68.9 ends/10cm
Pile Density	6,646 oz/yd <sup>3</sup>	246,432 g/m <sup>3</sup>
Size	9.845 in x 39.38 in	25cm x 1m
Performance Specifications		
Flooring Radiant Panel	(ASTM E-648) Passes	
Smoke Density	(ASTM E 662) ≤ 450	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's	
Static	(AATCC - 134) < 3.0 KV	
Dimensional Stability	AACHEN Din 54318 < 0.10%	
Traffic Classification	Heavy	
Fiber Modification Ratio	1.7 to 1.9	
Health + Environmental Specifications		
Carbon Footprint		
Embodied Carbon (Cradle to Gate)	-0.4 Kg CO <sub>2</sub> /M <sup>2</sup>	
Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™	
Total Recycled Content	19%	
Recycled Content (Pre Consumer)	18%	
Recycled Content (Post Consumer)	1%	
Indoor Air Quality	Green Label Plus #100244 CDPH 01350	
Material Composition	PVC-free and also free of Added Formaldehyde, Heavy Metals and Ortho Phthalates, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.	
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>	
Disclosure of Product Ingredients	Health Product Declaration	
LEED v4	Contributes to multiple IEQ and MR credits	
End of Life	Carpet to Carpet Recycling through ReEntry®	
Technical Information		
Installation	<a href="#">Interface Installation Guidelines</a>	
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>	
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)	
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>	

Installation Method	Herringbone,Ashlar
Standard Backing	CQuest™BioX
Backing Options ( <a href="#">Learn more</a> )	CQuest™BioX
Tile Size Options	25cm x 1m
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified facilities in Troup County, Georgia, United States</a>