



Installation Method



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Tokyo Texture **Color** 106622 Ash **Collection** Embodied Beauty **Backing** CQuest™BioX

[-CO2]

Product Specifications

Product Number	137460AK0Q	
Product Construction	Tufted Textured Loop	
Yarn System	Post-Consumer Content Nylon	
Yarn Manufacturer	Universal	
Dye Method	100% Solution Dyed	
Soil/Stain Protection	Protekt ² ®	
Preservative Protection	No Added Preservatives	
	Imperial	Metric
Tufted Yarn Weight	12 oz/yd ²	407 g/m ²
Machine Gauge	1/10 in	47.2 ends/10cm
Pile Height	0.13 in	3.2 mm
Pile Thickness	0.048 in	1.2 mm
Stitches	14.7 /in	57.9 ends/10cm
Pile Density	9,000 oz/yd ³	333,718 g/m ³
Size	9.845 in x 39.38 in	25cm x 1m

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Severe
Fiber Modification Ratio	1.7 to 1.9

Health + Environmental Specifications

Carbon Footprint	
Embodied Carbon (Cradle to Gate)	-0.4 Kg CO ₂ /M ²
Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™
Total Recycled Content	19%
Recycled Content (Pre Consumer)	18%
Recycled Content (Post Consumer)	1%
Indoor Air Quality	Green Label Plus #100244 CDPH 01350
Material Composition	PVC-free and also free of Added Formaldehyde, Heavy Metals and Ortho Phthalates, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration
LEED v4	Contributes to multiple IEQ and MR credits
End of Life	Carpet to Carpet Recycling through ReEntry®

Technical Information

Installation	Interface Installation Guidelines
Maintenance	Recommended Interface Maintenance Guidelines
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	15 Year Standard Carpet Warranty

Installation Method	Herringbone
Standard Backing	CQuest™BioX
Backing Options (Learn more)	CQuest™BioX
Tile Size Options	25cm x 1m
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States